

IN THE CLAIMS:

This **Listing of Claims** will replace all prior versions, and listings, of claims in the application:

Listing of Claims

1. (currently amended) A blocking device (30) for blocking a rotary motion of a shaft (14) relative to a housing (16) of a gear-drive unit (10) in a blocking state, the blocking device (30) having a first blocking element (32) and a second blocking element (34) which latter is displaceable relative to the first blocking element (32) by means of at least one electromagnet (44) and at least one restoring element (42), wherein the blocking elements (32, 34) each have a complete set of radially extending indentations (82) and radially extending raised areas (84), alternately and evenly positioned about an entire outer radial surface portion proximate each blocking element's circumferential edge,

wherein each radially extending indentation and raised area pair on one blocking surface is positioned to oppose each radially raised area and extending indentation pair on the other blocking surface, enabling the blocking elements to mesh with one another in an axial direction and in a form-locking fashion to block the rotary motion of the shaft (14) in the blocking state,

~~and~~ wherein the blocking device (30) is embodied as a separate, independent structural unit (31) comprising a barrier housing (52), which barrier

housing (52) is axially press fitted to mount the separate independent structural unit (31) that is mounted as a unit (31) onto and within the housing (16), and wherein the first blocking element (32) is embodied as a rotatable disk with radial moldings comprising an inner toothing (68) configured to engage corresponding counterpart moldings (70) comprising outer toothing (70) of a slaving means (66) located on the shaft (14) in a manner fixed against relative rotation, which slaving means (66) is thrust into the blocking element (32) to effect installation. on the one hand and onto the shaft (14) on the other.

2. (cancelled)

3. (cancelled)

4. (cancelled)

5. (previously presented) The blocking device (30) as defined by claim 1, characterized in that the electromagnet (44) is not supplied with current in the blocked state, and the second blocking element (34) is pressed in form-locking fashion into the first blocking element (32) by the at least one restoring element (42), and in the rotating state the electromagnet (44) is supplied with current, in order to detach the second blocking element (34) axially from the first blocking element (32).

6. (currently amended) The blocking device (30) as defined by claim 1, characterized in that ~~the a~~-barrier housing (52) is configured as a stop disk (60) forming ~~forms~~ at least one axial stop (74) for the first blocking element (32).

7. (previously presented) The blocking device (30) as defined by claim 6, characterized in that the first, rotatable blocking element (32) has axial extensions (62, 61, 63), which are braced on the at least one axial stop (60, 74) of the barrier housing (52).

8. (currently amended) The blocking device (30) as defined by claim 6, characterized in that the ~~various~~-axial extensions (62, 61, 63) are braced on both sides of the stop disk (60) in such a way that an axial engagement of the two blocking elements (32, 34) with one another in rotary operation is prevented.

9. (currently amended)) The blocking device (30) as defined by claim 6, characterized in that the axial extensions (62, 61, 63) form a detent hook (61) or a dome with a clamping or securing ring, or are radially deformed after being pushed through the stop disk (60).

10. (withdrawn) The blocking device (30) as defined by claim 1, characterized in that electrically conductive spring elements (89) operate as an

electrical contacting means (56) and extend in the axial direction and are located on one face end (88) of the electromagnet (44).

11. (previously presented) The blocking device (30) as defined by claim 1, characterized in that the electromagnet (44) is located in a coil holder (46), on which for axial guidance and/or prevention of relative rotation of the second blocking element (34), axial guide elements (78) - in particular pegs (78) - are integrally formed on, which engage corresponding counterpart elements (80) of the second blocking element (34).

12. (previously presented) The blocking device (30) as defined by claim 1, characterized in that at least the second blocking element (34) of the two blocking elements (32, 34) is made at least in part of plastic, such as an elastomer.

13. (withdrawn) A gear-drive unit (10), having a blocking device (30) as defined by claim 1, characterized in that a roller bearing (18) with an outer ring (90) and an inner ring (92) is located on the blocking device (30), and the outer ring (90) is braced on the housing (16), and the inner ring (92) receives the shaft (14) - in particular with a slaving means (66) located on it in a manner fixed against relative rotation.

14. (withdrawn) The gear-drive unit (10) as defined by claim 1, characterized in that the roller bearing (18), as part of the blocking device (30), is integrated solidly with the barrier housing (52).

15. (withdrawn) The gear-drive unit (10) as defined by claim 1, characterized in that the first, rotatable blocking element (32) is braced axially on the inner ring (92) of the roller bearing (18).

16. (withdrawn) The gear-drive unit (10) as defined by claim 1, characterized in that the first, rotatable blocking element (30) is braced axially on the shaft (14) - in particular on a collar (94) of the slaving means (66).

17. (withdrawn) The gear-drive unit (10) as defined by claim 1, characterized in that the first, rotatable blocking element (32) is braced axially elastically on the inner ring (92) and/or on the shaft (14) - for instance by means of an axial spring (96) - in order to compensate for longitudinal play of the shaft (14) that is supported axially loosely in the roller bearing (18).

18. (withdrawn) A method for producing a gear-drive unit (10) as defined by claim 1, characterized in that the blocking device (30) is first secured in the housing (16) of the gear-drive unit (10), and next the shaft (14) - in particular with the slaving means (66) - is introduced with a form lock that has play into a central

recess (64) in the first blocking element (32) - and in particular with a close clearance fit into the roller bearing (18).

19. (withdrawn) The method as defined by claim 18, characterized in that the blocking device (30) with the barrier housing (52) is built into the housing (16) of the gear-drive unit (10) in a manner fixed against relative rotation and in particular is axially secured by means of material deformation.

20. (withdrawn) The method as defined by claim 18, characterized in that the shaft (14) is positioned by means of a fixed bearing (18, 20) in the housing (16) in such a way that the first, rotatable blocking element (32) is pressed - in particular by means of the axial spring (96) - with a predeterminable prestressing force axially against the inner ring (92) of the roller bearing (18).

21. (withdrawn) The method as defined by claim 18, characterized in that before being built into the housing (16) and before the installation of the shaft (14) as a separate unit (31), enclosed by the barrier housing (52), the blocking device (30) is easily monitorable as to its function, in particular its power consumption.

22. (currently amended) A blocking device (30) for blocking a rotary motion of a shaft (14) relative to a housing (16) of a gear-drive unit (10) in a blocking state, the blocking device (30) comprising:

a first, rotatable blocking element (32);

a second blocking element (34);

at least one electromagnet (44); and

at least one restoring element (42);

wherein the second blocking element (34) is displaceable relative to the first blocking element (32) by means of the at least one electromagnet (44) and the at least one restoring element (42),

wherein the blocking device (30) is embodied as a separate, independent structural unit (31) comprising a barrier housing (52), which barrier housing (52) is axially press fitted to mount the separate independent structural unit (31) is ~~mounted-onto~~ and within the housing (16) on the one hand, ~~wherein and onto the~~ shaft (14) is passed through a central opening (64) fixing the blocking device (30) thereto on the other hand, and

wherein the a-barrier housing (52) is configured as a stop disk (60) forming forms at least one axial stop (74) for the first, rotatable blocking element (32), which first, rotatable blocking element (32) has axial extensions (62, 61, 63) that are braced on the at least one axial stop (60, 74) of the barrier housing (52) to mesh in the axial direction with one another by form-locking.